

Product Submittal Sheet

Product Category: Framing Accessory
 Product Name: Furring Channel
 Member: 087F125 - 18
 Thickness: 18 mil (25 ga)
 Coating: G40



Product Data:

*Picture is reference only; it may differ from the actual product

Top Flat	Depth	Coating	Weight	Design Thickness	Minimum Thickness
1.250 in	0.875 in	G 40	0.24 LB/FT	0.0188 in	0.0179 in

ASTM STANDARDS AND COMPLIANCE CODES

Meets or exceeds ASTM C645 and C754
 Hot dip coating per ASTM A924
 Steel sheet specification per ASTM A 1003.
 SDS Information Available at www.panelrey.com

LEED CREDITS

Leed v4 MR. Raw Material Supply.
 Leed v4 MR. Construction and Demolition Waste Management.
 Leed v3 MR2. Construction Waste Management. The steel used is 100 % recyclable.
 Leed v3MR4. Recycled Content. The steel used in the profiles has a minimum of

Total recycled content: 49%
 Post-Consumer recycled content: 37%
 Pre-Consumer recycled content: 12%

PROJECT INFORMATION	CONTRACTOR INFORMATION	ARCHITECT INFORMATION
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax:

SUB-NS087F12518.V2023-1.0