

# Product Submittal Sheet

Product Category: Framing Accessory  
 Product Name: Resilient Channel  
 Member: 045R110 - 18  
 Thickness: 18 mil (25 ga)  
 Coating: G40



\*Picture is reference only; it may differ from the actual product

## Product Data:

Top Flat	Depth	Coating	Weight	Design Thickness	Minimum Thickness
1.100 in	0.450 in	G 40	0.15 LB/FT	0.0188 in	0.0179 in

## ASTM STANDARDS AND COMPLIANCE CODES

Meets or exceeds ASTM C645 and C754  
 Hot dip coating per ASTM A924  
 Steel sheet specification per ASTM A 1003.  
 SDS Information Available at [www.panelrey.com](http://www.panelrey.com)

## LEED CREDITS

Leed v4 MR. Raw Material Supply.  
 Leed v4 MR. Construction and Demolition Waste Management.  
 Leed v3 MR2. Construction Waste Management. The steel used is 100 % recyclable.  
 Leed v3MR4. Recycled Content. The steel used in the profiles has a minimum of

**Total recycled content: 49%**  
 Post-Consumer recycled content: 37%  
 Pre-Consumer recycled content: 12%

PROJECT INFORMATION	CONTRACTOR INFORMATION	ARCHITECT INFORMATION
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax:

SUB-NS045R11018.V2023-1.0