



## QUALITY CERTIFICATE

**Client:**

**Date:**

**Product:**

This document certifies that Panel Rey® S.A. manufactures the drywall:

1/4" Flex Rey	1/2" Guard Rey	5/8" Guard Rey Type X
3/8" Regular	1/2" Exterior	5/8" Exterior Type X
1/2" Regular	1/2" Fire Rey Type X	
1/2" Light Rey	5/8" Fire Rey Type C	

Achieves or exceeds the ASTM-C1396 parameters, which are evaluated according to the ASTM C-473; therefore, the acceptance values for the preview's characteristics are warranted.

- Length Tolerance.
- Core Hardness.
- Edge Hardness.
- Tapered Edge Depth.
- Flexural Strength (Parallel to fiber).
- Flexural Strength (Across to fiber).
- Nail Pull Resistance.
- Nominal Thickness
- Wet flexural strength.
- End Squareness.

In addition, 5/8 " thick drywall has been subjected to different tests for fire resistance, smoke generation and flame spread according to ASTM E119 and ASTM E84 respectively and are classified by Underwriters Laboratories (UL).

The warranty for these products is limited to product performance quality and not to external situations; such as structural failures or deficiencies attributable to the construction design; it can occur before, during and/or after installation.

Panel Rey® S. A. always seeks to maintain the confidence of its clients by manufacturing and providing high quality products which meet or exceed ASTM standards and other international regulations.

A handwritten signature in black ink, appearing to read "Oscar Mendez Mena", is written over a circular stamp or seal.

**Oscar Mendez Mena**

**Quality Assurance.**

**Panel Rey S. A.**