

ULTIMA PLUS

Customer Service USA 1800 862 9022
www.panelrey.com

Manufacturer

Planta PANEL REY
Carretera Monterrey-Monclova km 11.5
El Carmen, NL. CP. 66560
Serafín Peña # 938 Sur C.P. 64000
Monterrey, Nuevo León. Phone: 1 800 862 9022

Description

Ultima Plus Compound is the best option for a smooth, manageable application and sliding. It is extremely easy to sand due to its properties of low density ready mix. This is a totally different product, since it is 20% lighter than traditional compounds. It offers a higher coverage and efficiently reduces shrinkage and cracks.

Basic uses

For treating joints and accessories, textures and final finishing in corners and edges, as well as for repairing screw and nail heads.

Advantages

- More coverage.
- Smooth application.
- Less shrinkage.
- Optimum drying time.

Limitations

- Drying time may vary depending on the weather conditions.
- All surfaces must be dry, clean and free of grease or dust.
- Keep proper ventilation in the work area to eliminate excess moisture.

Storage

Joint compounds and finishing products have a ten-month warranty, effective from the date of manufacture, and when stored under normal conditions, and in protected places. Do not stack more than two pallets high.

Caution

Avoid dust from damp sanding. Use a mask and safety goggles. Dust resulting from sanding may irritate eyes, nose or throat. In the event of visual contact, thoroughly wash with water for 15 minutes until all particles are removed. If irritation persists, get medical attention. Do not ingest this product. KEEP OUT OF THE REACH OF CHILDREN. For more safety information refer to the SDS on Panel Rey's website.

Greenguard Certified

Product certified for low chemical emissions.
UL.COM/GG UL 2818

Preparation

Mix contents uniformly without adding water for covering fasteners and corner bead. For taping and finishing joints, thin as necessary by adding clean water especially for use in mechanicals tools. Do not add more than 2% (by weight of product) of water because it may cause cracking and bonding problems. Re-mix uniformly after thinning. Do not mix with other products. This product is manufactured to meet requirements established in ASTM-C475.

Composition

The compound is made of vinyl adhesives and other additives: it can be applied directly from the packaging, manually or with mechanical equipment, and meets the ASTM C-475 Standard in accordance to the ASTM C-474 Standard procedures. For your safety, Panel Rey® products do not contain asbestos.

General Application

COVERING JOINTS AND APPLYING THE FIRST LAYER

Apply Ultima Plus compound over joints with a 6" knife. Immediately put joint tape over covered area use the same knife to remove any excess of compound over the joint tape. Apply first layer of compound over the tape with an 8" knife.

APPLYING THE SECOND AND THIRD LAYER

After the first layer of Ultima Plus compound is completely dry apply a second layer with the 10" knife over the tape, and once dried, proceed with a third layer of Ultima Light using the 12" knife.

FINISH

The total width of the joint treatment should be not less than 12". After the third layer is completely dry, softly sand over joints, removing any excess of dry compound and leaving a dust-free surface ready for the final finishing. Nails, screw heads, corner beads, archways and any other accessories must be treated as well three layers of Ultima Plus compound.

COVERAGE	7.3 ft ² /lb (1.5m ² /kg)	
Carton	38 lb (17.4 kg)	3.75 gal (14.2 L)



SUBMITTAL APPROVALS

Job Name _____
Contractor _____
Date _____

* For complete warranty details, visit www.panelrey.com

Stamps/Signatures