

Ultima Light Dustbuster

Description:

Ultima light Dustbuster from Panel Rey[®] is a multipurpose joint compound that is easy to apply and has an excellent finish. It produces less dust in the air during sanding, reducing the impact in the Interior Air Quality. It is specially designed to provide a smooth application with an easy sanding. It is 20% lighter than traditional compounds and offers a greater coverage with less cracking and shrinkage. This product is ideal for projects that demand high quality.

Advantages:

- ✓ Ultima Light Dustbuster From Panel Rey[®] reduces in more than 50% the dust from sanding.
- ✓ The dust low emissions improve the Interior Air Quality, it saves time and makes the cleaning easier.
- ✓ Its properties make it ideal for joint finishing treatment and achieving a smoother surface.
- ✓ High adherence
- ✓ Low Shrinkage

Product Data:

Coverage: 0.63 kg/m² Availability: 17.4 kg box

Applications:

- ✓ Treating joints and accesories.
- ✓ Final coats.
- ✓ Cracking repairs.
- ✓ Interior texture.



Preparation:

Before Beginning, verify that all surfaces are dry, clean and free of grease or dust that inhibit the correct adherence to the drywall. Mix the content before applying. For taping and finishing joints, thin as necessary by adding clean water. Do not add more than 2% (by weight of product) of water because it may cause cracking and bonding problems. This product meets the requirements of the ASTM-C475.

General Application:

First Coat

With a 6" joint knife apply the compound all over the drywall's joint. Place the tape along the joint, press it and remove the overage. Then immediately apply a first coat of compound with the 8" taping knife. Afterwards cover screw heads, fasteners and accessories.

Second and Third Coat

When the compound is completely dry, approximately 8 hours later, apply a second coat with a 10" taping knife then smooth the surface. Repeat the same process for the third coat with a 12" taping knife. Screw heads, fasteners and accessories must be cover with three coats of compound. For more information check GA-236 manual.

Finishing

At the end of the third coat, the joint treatment should be 12" width. After the last coat has dried, lightly sand the joint and the covered accessories, leaving the wall ready for the final finish.

Storage:

Store in a fresh and dry place. Do not stack more than two pallets high. Protect from freeze and extreme heat. The product warranty is 9 months after the date of manufacture.

Caution:

All surfaces must be dry, clean and free of grease or dust, that could inhibit the correct adherence to the drywall. Thin as necessary by adding clean water avoiding overage. Ensure that the compound temperature, environment and application surface exceed 10° C and maintain an adequate workplace ventilation to eliminate the moisture excess. Use a mask and safety goggles. Despite the high decrease of dust generation, dust resulting from sanding may irritate eyes, nose or throat. Do not ingest this product. KEEP OUT OF THE REACH OF CHILDREN.

Panel Rey México, S. A. Mantiene la facultad de ejercer modificaciones a la información de este documento sin previo aviso. No es posible tener en cuenta toda la normatividad relacionada con el producto, por lo tanto, el usuario debe tener en cuenta estas normas. Todas las reclamaciones deben de estar por escrito y sustentadas con evidencia; se deben de enviar en un período no mayor a 30 días naturales a partir de la fecha en que se descubrió o debió haberse descubierto el defecto y debe de estar dentro del período de garantía del producto. El cliente no debe de alterar o reparar el área afectada hasta que Panel Rey haya revisado el problema y determine una posible causa. La responsabilidad de Panel Rey México, S. A. se limita únicamente a la reposición del material defectuoso y no se hace responsable de los daños fortuitos e imprevistos, directos o indirectos, ni por cualquier pérdida causada por la aplicación de estos productos que no vaya acorde con las instrucciones o con el uso intencionado, así como la aplicación del producto posterior a la fecha de caducidad.

For more information contact us:

Customer Service USA

1 800 862 9022

Phone

+52 (81) 8345-0055

E-mail

contact.us@gpromax.com

Web Site

www.panelrey.com

