

# Taping & Topping Compound

## Description:

Panel Rey<sup>®</sup> Topping compound is specifically designed for topcoat applications, has the advantage of low shrinkage, smooth application and easy sanding. This product is ideal for projects that demand high quality and efficiency.

## Advantage:

- It is ideal for the final finishing process.
- Low shrinkage
- Resistant to cracking
- Smooth application
- Easiest sanding
- Tinted

## Product data:

- Presentation : Box 3.5 gal

## Applications

- Final finish
- Texturing indoors
- Heal superficial cracks

## Preparation

Before starting, verify that all surfaces are dry, clean and free of grease or dust that prevents proper adhesion to the substrate. Mix before use. For tapes and finishing applications only, you can add up to 2% water to the weight of the product. Too much water can cause cracking or spalling. This product is manufactured under the ASTM C-475 standard.



## How to use

### First to layer

Using a 6 "spatula, apply the compound to the joint formed by the drywall. Place the reinforcing tape on the joint and press with the spatula, removing the excess. Immediately afterwards apply a first coat of compound on the tape with a spatula of 8 ". Cover screw heads, corner pieces and accessories.

### Second and third to layer

When the compound is completely dry, approximately 8 hours later, apply the second coat with a 10 "putty knife, smoothing the surface. Repeat for a third coat with the 12" putty knife. Screw heads, corner pieces, and accessories must be covered with three coats of compound. For more information, see manual GA- 236.

### Finish

At the end of the third coat, the joint treatment should be 30 cm wide. After the last coat has dried, lightly sand the joint and covered fittings, preparing the wall for a final finish.

### Storage

Store in a fresh and dry place. Do not stow more than two pallets in height. Protect from freezing or extreme heat. The warranty date of the product is 9 months after its manufacturing date.

### Precautions

All surfaces must be dry, clean and free of grease or dust that could prevent proper adhesion to the substrate. Use clean water to lose weight and mix the products when desired, avoiding overdoing it. Ensure that the temperature of the paste, environment and application surface exceed 10 ° C and maintain adequate ventilation of the work area that eliminates excess humidity.

Use mask and lenses of safety. Despite the high dis-comminution in the generation of dust, the dust created in the sanding may cause eye, nose or throat. Do not ingest the product. KEEP OUT OF REACH OF CHILDREN.

For more information contact us:

Customer Service USA

1 800 862 9022

Phone

+52 (81) 8345-0055

E-mail

contact.us@gpromax.com

Web Site

www.panelrey.com

Panel Rey México, SA Maintains the power to make modifications to the information in this document without prior notice. It is not possible to take into account all the regulations related to the product, therefore, the user must take these regulations into account. All claims must be in writing and supported by evidence; They must be sent within a period of no more than 30 calendar days from the date the defect was discovered or should have been discovered and must be within the product's warranty period. The client should not alter or repair the affected area until Panel Rey has reviewed the problem and determined a possible cause. The responsibility of Panel Rey México, SA is limited solely to the replacement of defective material and is not responsible for incidental and unforeseen direct or indirect damages, nor for any loss caused by the application of these products that is not in accordance with the instructions or with the intended use, as well as the application of the product after the expiration date.



**PANEL REY**  
Drywall Solutions

